

# ADJUSTABLE BAYONET STYLE THERMOCOUPLES AND RTDS

A  -  -  -  -

| 5. OPTIONS |   |
|------------|---|
| U          | Ungrounded (3/16" OD Standard)                    |
| AA         | Special Construction, Describe                    |
| 29         | 1/8" Diameter Probe                               |
| 39         | 3/16" Diameter Probe                              |
| 99         | Fiberglass Wire Without Stainless Steel Overbraid |

| 4. TERMINATION TYPE |  |
|---------------------|--|
| 0                   | Leads Not Stripped                               |
| 1                   | Standard Male Plug                               |
| 2                   | Standard Female Jack                             |
| 3                   | BX Connector & 4" Stripped Leads with Spade Lugs |
| 4                   | 4" Stripped Leads with Spade Lugs                |

**3. B" LENGTH**  
Specify in Inches

| 2. CALIBRATION TYPE |                        |
|---------------------|------------------------|
| J                   | Iron/Constantan        |
| K                   | Chromel/Alumel         |
| T                   | Copper/Constantan      |
| RTD2                | 100 Ohm, 2 Wire        |
| RTD3                | 100 Ohm, 3 Wire        |
| RTD4                | 100 Ohm, 4 Wire        |
| JJ                  | Dual Iron/Constantan   |
| KK                  | Dual Chromel/Alumel    |
| TT                  | Dual Copper/Constantan |
| RTD/RTD2            | Dual 100 Ohm, 2 Wire   |
| RTD/RTD3            | Dual 100 Ohm, 3 Wire   |
| RTD/RTD4            | Dual 100 Ohm, 4 Wire   |

| 1. THERMOCOUPLE STYLE |                                  |
|-----------------------|----------------------------------|
| A500                  | Armored Adjustable Bayonet Style |
| A510                  | Spring Adjustable Bayonet Style  |