

# PROBE STYLE TUBE AND WIRE THERMOCOUPLES AND RTDS

A 1 - 2 - 3 - 4 - 5 - 6

6. OPTIONS	
U	Ungrounded (3/16" OD Standard)
W	Welded Construction
29	1/8" Diameter Probe
39	3/16" Diameter Probe
99	Fiberglass Wire Without Stainless Steel Overbraid
AA	Special Construction, Describe

5. TERMINATION TYPE	
0	Leads Not Stripped
1	Standard Male Plug
2	Standard Female Jack
3	BX Connector & 4" Stripped Leads with Spade Lugs
4	4" Stripped Leads with Spade Lugs

4. "B" LENGTH  
Specify in Inches

3. "A" LENGTH  
Specify in Inches

2. CALIBRATION TYPE	
J	IRON / CONSTANTAN
K	CHROMEL / ALUMEL
T	COPPER / CONSTANTAN
RTD2	100 OHM, 2 WIRE
RTD3	100 OHM, 3 WIRE
RTD4	100 OHM, 4 WIRE
JJ	DUAL IRON / CONSTANTAN
KK	DUAL CHROMEL / ALUMEL
TT	DUAL COPPER / CONSTANTAN
RTD/RTD2	DUAL 100 OHM, 2 WIRE
RTD/RTD3	DUAL 100 OHM, 3 WIRE
RTD/RTD4	DUAL 100 OHM, 4 WIRE

1. THERMOCOUPLE STYLE	
A520	Probe Style Tube and Wire