

FIXED BAYONET THERMOCOUPLES AND RTDs

A

1	2	-	3	-	4	-	5	-	6
---	---	---	---	---	---	---	---	---	---

6. OPTIONS	
U	Ungrounded (3/16" OD Standard)
W	Welded Construction
29	1/8" Diameter Probe
49	1/4" Diameter Probe
09	Fiberglass Wire with Stainless Steel Overbraid
99	Fiberglass Wire without Stainless Steel Overbraid
AA	Special Construction, Describe

5. TERMINATION TYPE	
0	Leads Not Stripped
1	Standard Male Plug
2	Standard Female Jack
3	BX Connector & 4" Stripped Leads with Spade Lugs
4	4" Stripped Leads with Spade Lugs

4. "B" LENGTH
Specify in Inches

3. "A" LENGTH
Specify in Inches

2. CALIBRATION TYPE	
J	Iron/Constantan
K	Chromel/Alumel
T	Copper/Constantan
RTD2	100 Ohm, 2 Wire
RTD3	100 Ohm, 3 Wire
RTD4	100 Ohm, 4 Wire
JJ	Dual Iron/Constantan
KK	Dual Chromel/Alumel
TT	Dual Copper/Constantan
RTD/RTD2	Dual 100 Ohm, 2 Wire
RTD/RTD3	Dual 100 Ohm, 3 Wire
RTD/RTD4	Dual 100 Ohm, 4 Wire

1. THERMOCOUPLE STYLE	
A100	Straight Fixed Bayonet Style
A145	45° Fixed Bayonet Style
A190	90° Fixed Bayonet Style