

THERMOCOUPLE AND RTD EXTENSION CABLES

A - - - - -

6. OPTIONS	
9	Fiberglass Wire With Stainless Steel Overbraid
99	Fiberglass Wire Without Stainless Steel Overbraid (no armor)
AA	Special Construction, Describe

5. "Y" TERMINATION	
0	Leads Not Stripped
1	Standard Male Plug
1M	Miniature Male Plug
2	Standard Female Jack
2M	Miniature Female Jack
3	BX Connector & 4" Stripped Leads with Spade Lugs
4	4" Stripped Leads with Spade Lugs

4. "X" TERMINATION	
0	Leads Not Stripped
1	Standard Male Plug
1M	Miniature Male Plug
2	Standard Female Jack
2M	Miniature Female Jack
3	BX Connector & 4" Stripped Leads with Spade Lugs
4	4" Stripped Leads with Spade Lugs

3. "B" LENGTH	
Specify in Inches	

2. CALIBRATION TYPE	
J	IRON / CONSTANTAN
K	CHROMEL / ALUMEL
T	COPPER / CONSTANTAN
RTD2	100 OHM, 2 WIRE
RTD3	100 OHM, 3 WIRE
RTD4	100 OHM, 4 WIRE
JJ	DUAL IRON / CONSTANTAN
KK	DUAL CHROMEL / ALUMEL
TT	DUAL COPPER / CONSTANTAN
RTD/RTD2	DUAL 100 OHM, 2 WIRE
RTD/RTD3	DUAL 100 OHM, 3 WIRE
RTD/RTD4	DUAL 100 OHM, 4 WIRE

1. THERMOCOUPLE STYLE	
A800	Armored Extension Cable
A810	Stainless Steel Over Braid Extension Cable