

FIXED COMPRESSION THERMOCOUPLES AND RTDs

A 1 - 2 - 3 - 4 - 5 - 6

6. OPTIONS	
U	Ungrounded (3/16" OD Standard)
W	Welded Construction
00	No Compression Fitting Required
29	1/8" Diameter Probe
49	1/4" Diameter Probe
09	Fiberglass Wire With Stainless Steel Overbraid
99	Fiberglass Wire Without Stainless Steel Overbraid
AA	Special Construction, Describe

5. TERMININATION TYPE	
0	Leads not Stripped
1	Standard Male Plug
2	Standard Female Plug
3	BX Connector and 4" Stripped Leads with Spade Lugs
4	4" Stripped Leads with Spade Lugs

4. "B" LENGTH
Specify in Inches

3. "A" LENGTH
Specify in Inches

2. CALIBRATION TYPE	
J	Iron/Constantan
K	Chromel/Alumel
T	Copper/Constantan
RTD2	100 Ohm, 2 Wire
RTD3	100 Ohm, 3 Wire
RTD4	100 Ohm, 4 Wire
JJ	Dual Iron/Constantan
KK	Dual Chromel/Alumel
TT	Dual Copper/Constantan
RTD/RTD2	Dual 100 Ohm, 2 Wire
RTD/RTD3	Dual 100 Ohm, 3 Wire
RTD/RTD4	Dual 100 Ohm, 4 Wire

1. THERMOCOUPLE STYLE	
A200	Straight Fixed Compression Style
A245	45° Fixed Compression Style
A290	90° Fixed Compression Style