

NOZZLE STYLE THERMOCOUPLES AND RTDS

A - - - -

5. OPTIONS	
U	Ungrounded
99	Fiberglass Wire Without Stainless Steel Overbraid
AA	Special Construction, Describe
B1	6 x 1.0 x 10mm bolt
B2	8 x 1.25 x 16mm bolt
SS	Stainless Steel Bolt

4. TERMINATION TYPE	
0	Leads Not Stripped
1	Standard Male Plug
2	Standard Female Jack
3	BX Connector and 4" Stripped Leads with Spade Lugs
4	4" Stripped Leads with Spade Lugs

3. B" LENGTH
Specify in Inches

2. CALIBRATION TYPE	
J	IRON / CONSTANTAN
K	CHROMEL / ALUMEL
T	COPPER / CONSTANTAN
RTD2	100 OHM, 2 WIRE
RTD3	100 OHM, 3 WIRE
RTD4	100 OHM, 4 WIRE
JJ	DUAL IRON / CONSTANTAN
KK	DUAL CHROMEL / ALUMEL
TT	DUAL COPPER / CONSTANTAN
RTD/RTD2	DUAL 100 OHM, 2 WIRE
RTD/RTD3	DUAL 100 OHM, 3 WIRE
RTD/RTD4	DUAL 100 OHM, 4 WIRE

1. THERMOCOUPLE STYLE	
A300	Armored Nozzle Style
A310	Spring Relief Nozzle Style