

PLASTIC MELT THERMOCOUPLES AND RTDS

A - - - - -

6. OPTIONS

U	Ungrounded (3/16" OD Standard)
AA	Special Construction, Describe

5. TERMINATION TYPE

0	Leads Not Stripped
1	Standard Male Plug
2	Standard Female Jack
3	BX Connector & 4" Stripped Leads with Spade Lugs
4	4" Stripped Leads with Spade Lugs

4. "B" LENGTH

3	3" SS Melt Bolt
4	4" SS Melt Bolt
6	6" SS Melt Bolt
8	8" SS Melt Bolt
10	10" SS Melt Bolt
12	12" SS Melt Bolt

3. "A" LENGTH
Specify in Inches

--	--

2. CALIBRATION TYPE

J	Iron/Constantan
K	Chromel/Alumel
T	Copper/Constantan
RTD2	100 Ohm, 2 Wire
RTD3	100 Ohm, 3 Wire
RTD4	100 Ohm, 4 Wire
JJ	Dual Iron/Constantan
KK	Dual Chromel/Alumel
TT	Dual Copper/Constantan
RTD/RTD2	Dual 100 Ohm, 2 Wire
RTD/RTD3	Dual 100 Ohm, 3 Wire
RTD/RTD4	Dual 100 Ohm, 4 Wire

1. THERMOCOUPLE STYLE

A400	Plastic Melt Style
A410	Adjustable Melt Style