


Mgo THERMOCOUPLES [5]



| 5. ELEMENT FITTING | |
|--------------------|--|
| CODE | DESCRIPTION |
| 00 | NO ELEMENT MOUNTING FITTING |
| 01 | STAINLESS STEEL, ONE TIME ADJUSTABLE COMPRESSION FITTING |
| 02 | STAINLESS STEEL, ONE TIME ADJUSTABLE COMPRESSION FITTING |
| 05 | STAINLESS STEEL, ONE TIME ADJUSTABLE COMPRESSION FITTING |
| 09 | STAINLESS STEEL, RE-ADJUSTABLE COMPRESSION FITTING |
| 12 | STAINLESS STEEL, RE-ADJUSTABLE COMPRESSION FITTING |
| 14 | ADJUSTABLE STEEL FLANGE WITH BRASS COMPRESSION FITTING |
| 15 | BRASS, ADJUSTABLE COMPRESSION FITTING |
| 18 | 304 STAINLESS STEEL WELD PAD (1" X 1" X 1/8" THICK STANDARD) |
| 19 | BRASS, ADJUSTABLE SPRING LOADED WELL FITTING |
| 25 | BRASS, ADJUSTABLE COMPRESSION FITTING |
| 20(X) | BAYONET CAP AND SPRING (SPECIFY "X" DIMENSION) |
| 21(X) | FIXED STAINLESS STEEL BUSHING (SPECIFY "X" DIMENSION) |
| 23(X) | FIXED STAINLESS STEEL BUSHING (SPECIFY "X" DIMENSION) |
| 24(X) | FIXED STAINLESS STEEL BUSHING (SPECIFY "X" DIMENSION) |
| 25(X) | FIXED STAINLESS STEEL BUSHING (SPECIFY "X" DIMENSION) |
| AA | SPECIAL FITTING, DESCRIBE |