


RESISTANCE TEMPERATURE DETECTORS [1 to 3]



4 TO 8: SEE PAGES C-33 TO C-40

| 4. SHEATH AND OTHER OPTIONS | |
|-----------------------------|--|
| CODE | DESCRIPTION |
| A | HIGH ACCURACY BULB (±0.01% ACCURACY) |
| C | FIRST RESPONSE COPPER SHEATH |
| H | HIGH TEMP BULB (400°F / 204°C) (0.1% ACCURACY ONLY) |
| P | BLACK PVC COATING ON SHEATH |
| T | CLEAR TEFLON COATING ON SHEATH |

2. SHEATH LENGTH
INSERT 3 DIGIT LENGTH IN INCHES

| 1. CALIBRATION, TUBE DIAMETER AND MATERIAL | | | | | |
|--|----------|-----------|-----------|-----------|-----------|
| ACCURACY AT 0° C | MATERIAL | 1/8" OD | 3/16" OD | 1/4" OD | 3/8" OD |
| SINGLE ORDER CODE NUMBERS | | | | | |
| ± .03% | 316 SS | RTD28 | RTD38 | RTD48 | RTD68 |
| DUAL ORDER CODE NUMBERS | | | | | |
| ± .03% | 316 SS | RTD/RTD28 | RTD/RTD38 | RTD/RTD48 | RTD/RTD68 |

*RTDS COME STANDARD AS 3-WIRE (2 RED, 1 WHITE),
2 AND 4 WIRE ARE AVAILABLE UPON REQUESTED