


HIGH TEMPERATURE CERAMIC FIBER THERMOCOUPLE WIRE



- - - - - 3 5 0

CALIBRATION	
CODE	CODE
E	
J	
K	
N	

WIRE GAUGE	
CODE	
16	
16	
18	
20	
24	

CONDUCTOR TYPE / TOLERANCE	DESCRIPTION
1	THERMOCOUPLE GRADE, SOLID WIRE, STANDARD TOLERANCES
2	THERMOCOUPLE GRADE, SOLID WIRE, SPECIAL TOLERANCES
3	THERMOCOUPLE GRADE, STRANDED WIRE, STANDARD TOLERANCES
4	THERMOCOUPLE GRADE, STRANDED WIRE, SPECIAL TOLERANCES

SPECIFICATIONS

CONTINUOUS TEMPERATURE RATING 2200° F (1205° C)

SINGLE READING 2600° F (1430° C)

CONSTRUCTION CERAMIC FIBER BRAID SINGLE CONDUCTOR AND DUPLEX INSULATION.
NO IMPREGNATION FOR CONTAMINATION-FREE OPERATION.

APPLICATIONS STEEL AND ALUMINUM PLANTS
HEAT TREATING

RESISTANCE PROPERTIES			
TEMP.	MOISTURE	CHEMICAL	ABRASION
2200° F (1205° C)	FAIR	GOOD	GOOD