

PVC INSULATED THERMOCOUPLE AND EXTENSION WIRE

- - 5 0 2



CALIBRATION	
CODE	CODE
B	S
C	T
E	/
J	/
K	/
N	/

WIRE GAUGE	
CODE	
14	
16	
18	
20	
24	

CONDUCTOR TYPE / TOLERANCE	
CODE	DESCRIPTION
1	THERMOCOUPLE GRADE, SOLID WIRE, STANDARD TOLERANCES
2	THERMOCOUPLE GRADE, SOLID WIRE, SPECIAL TOLERANCES
3	THERMOCOUPLE GRADE, STRANDED WIRE, STANDARD TOLERANCES
4	THERMOCOUPLE GRADE, STRANDED WIRE, SPECIAL TOLERANCES
5	EXTENSION GRADE, SOLID WIRE, STANDARD TOLERANCES
6	EXTENSION GRADE, SOLID WIRE, SPECIAL TOLERANCES
7	EXTENSION GRADE, STRANDED WIRE, STANDARD TOLERANCES
8	EXTENSION GRADE, STRANDED WIRE, SPECIAL TOLERANCES

SPECIFICATIONS

CONTINUOUS TEMPERATURE RATING 220° F (105° C)

SINGLE READING N/A

CONSTRUCTION EXTRUDED PVC SINGLE CONDUCTOR AND DUPLEX INSULATION FOR EXCELLENT
MOISTURE RESISTANCE

APPLICATIONS LABORATORIES
INDUSTRIAL EQUIPMENT TESTING
AUTOMOTIVE

RESISTANCE PROPERTIES			
TEMP.	MOISTURE	CHEMICAL	ABRASION
220° F (105° C)	EXCELLENT	EXCELLENT	EXCELLENT