

# Material Safety Data Sheet

## W206 Silicone Mold Release™

# Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538	Product Name:	Silicone Mold Release™
	Product Code:	W206
	Version Date:	05/16/12
	24-hour emergency phone:	1-800-424-9300 [CHEMTREC]

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS #	ACGIH TLV	OSHA PEL	OTHER
Halogenated hydrocarbon/ether blend	Mixture	Not established	Not established	Not established
NJ Trade Secret Registry	#80100382-5037P	Not established	Not established	Not established

### 3. HAZARDS IDENTIFICATION

#### POTENTIAL ACUTE [single or short term] HEALTH EFFECTS OF OVEREXPOSURE

Eye : May cause eye irritation. Symptoms may include stinging, tearing, and redness.  
Skin : Liquid may cause frostbite.  
Ingestion : Ingestion is not considered a potential route of exposure. No evidence of harmful effects from available information.  
Inhalation : Breathing small amounts during handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Inhalation of concentrations above the recommended limits may cause temporary central nervous system depression with anesthetic effects such as dizziness, headache, incoordination, and loss of consciousness. Exposure to high concentrations can cause irregular heartbeat, cardiac arrest and death.

#### POTENTIAL CHRONIC [long term] HEALTH EFFECTS OF OVEREXPOSURE:

General Effects: Overexposure to vapor, dust or mist may aggravate existing respiratory conditions, such as asthma, bronchitis, and inflammatory or fibrotic respiratory disease.

Cancer Information: THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

#### MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Individuals with preexisting diseases of the central nervous or cardiovascular system may have increased susceptibility to the toxicity of excessive exposures.

#### HMS® III\* HAZARDOUS WARNINGS:

Health: 1 Flammability: 2 Physical: 1 Personal Protective Equipment: See Section 8

\* See [www.paint.org/hmis](http://www.paint.org/hmis) or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

### 4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.  
Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.  
Ingestion: Ingestion is an unlikely route of exposure. Contact a physician, medical facility, or poison control center for advice on whether to induce vomiting. Never give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing.  
Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.

#### NOTES TO PHYSICIAN:

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support.

### 5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Containers may rupture or explode under fire conditions. Hazardous decomposition products may be formed (see Sec.10).  
Fire Fighting Instructions: Use CO<sub>2</sub>, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.  
Aerosol Flame Projection Test: Non-flammable aerosol, as determined by ASTM D3065-94. However, this product contains components which may be ignited under certain circumstances. Do not use near ignition sources such as sparks or open flames.

### 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. If runoff occurs, notify authorities as required.

### 7. HANDLING AND STORAGE

Handling: Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Normal precautions common to safe manufacturing practice should be followed in handling and storage.  
Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 120 degrees F. Empty container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion

(oxidizing materials) and corrosive materials (strong acids or bases). Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Ground all equipment and cylinders before use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated in "Section 2" of this MSDS (from known, suspected or apparent adverse effects).
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Vapor Density:	[air = 1] 1.97
Appearance:	Clear Colorless	Evaporation Rate:	0.1-0.5 (n-Butyl acetate = 1)
Odor:	Slight ethereal.	Solubility in Water:	Negligible; 0-1%
Specific Gravity:	0.80 (H <sub>2</sub> O=1)	Boiling Point:	Not applicable°F
Vapor Pressure:	78.00 PSIG @ 70°F	pH:	Not applicable

## 10. STABILITY AND REACTIVITY

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Alkali. Alkaline earth metals. Freshly abraded aluminum surfaces. Powdered metals. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Oxidizers. Acetic acids Organic acid anhydrides.
Decomposition Products:	This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. If heated with peroxides present, violent decomposition can occur. Burning can produce the following combustion products: Carbon dioxide and carbon monoxide.

## 11. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

## 12. TRANSPORTATION INFORMATION

Agency	Proper Shipping name	UN Number	Hazard Class	Packing Group
DOT	Consumer commodity	Not applicable	ORM-D	Not applicable
IATA	Consumer commodity	Not applicable	9	Not applicable

## 13. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.

No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.

No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

**This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.**