CONNECTION HEAD AND TRANSMITTER SELECTION GUIDE

	TEMPERATURE TRANSMITTER				
	T-440	T-441	T-442	T-642	T-642 W/ DISPLAY
	Input: Pt100 RTD	Input: Thermocouple, Pt100 RTD, Other	Input: Thermocouple, Pt100 RTD, Other	Input: Thermocouple, Pt100 RTD, Other	Input: Thermocouple, Pt100 RTD, Other
	Programmable Head mounted transmitter, (4 to 20) mA analog output	Programmable Head mounted transmitter, Isolated, (4 to 20)mA analog output	Programmable Head mounted transmitter, Isolated, HART® protocol (4 to 20)mA analog output	Programmable Head mounted transmitter, Isolated, HART® protocol (4 to 20)mA analog output	Programmable field transmitter, dual input, Isolated, HART® protocol (4 to 20)mA analog output with digital output
CONNECTION HEADS					
Cast Iron / Aluminum Explosion Proof Head Group C	✓				
DIN form B Aluminum Explosion Proof Head Group B		✓	✓		
DIN form B Aluminum Explosion Proof Head Group A		✓	✓		
DIN form B Aluminum Explosion Proof Field Transmitter Housing Group A				✓	✓
316L Stainless Steel Explosion Proof Head Group C	✓				
DIN form B 316 Stainless Steel Head Group B		✓	✓		